


Borough of Red Bank  
Fire Marshals Office/Code Enforcement  
90 Monmouth Street, Red Bank, NJ 07701  
(732)-530-2764  
(732)-530-2766 (FAX)

APPLICATION AND  
CERTIFICATION IN LIEU OF  
INSPECTION FOR CERTIFICATE  
OF SMOKE ALARM AND CARBON  
MONOXIDE ALARM AND PORTABLE  
FIRE EXTINGUISHER COMPLIANCE



Dwelling Location: Block: \_\_\_\_\_ Lot: \_\_\_\_\_  
(not mailing address) Street: \_\_\_\_\_

Municipality: \_\_\_\_\_ County: Monmouth

\*NOTE: ALL BOXES MUST BE CHECKED IN ORDER FOR CERTIFICATION TO BE VALID

- Smoke alarm on each level of the dwelling, including basements, excluding attic or crawl spaces; and inside each bedroom
- Smoke alarm and carbon monoxide alarm outside each separate sleeping area; and within 10 feet of bedrooms
- All smoke alarm(s) are in working order.  Carbon monoxide alarm(s) are in working order
- Fire extinguisher is the correct size, is properly mounted, and is located within 10 feet of the kitchen

This is a \_\_\_\_\_ story dwelling  with  without a basement.

An inspection shall be conducted by the owner or an authorized representative of the owner. The smoke alarms required above shall be located in accordance with NFPA 72; the carbon monoxide alarm(s) installed per NFPA-720. The alarms are not required to be interconnected. 10 Year Sealed Battery Single Station powered alarms are required. Note: AC powered interconnected smoke alarms and carbon monoxide alarms installed in homes constructed after January, 1977 shall be maintained in working order but not older than 10 years. The fire extinguisher is installed per P.L. 2005, c.71 (N.J.S.A. 52:27D-198.1 et seq). See details on the back of this application for further information regarding installation.

Please mail certificate to: \_\_\_\_\_ Phone #: \_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_ Fax #: \_\_\_\_\_  
\_\_\_\_\_ Zip: \_\_\_\_\_

Contact person: \_\_\_\_\_ Phone #: \_\_\_\_\_ Closing Date: \_\_\_\_\_

I do hereby certify that the foregoing statements made by me are true. I am aware that if any of the foregoing statements made by me are willfully false, I will be subject to penalty.

Sworn and subscribed to before me this \_\_\_\_\_ day of \_\_\_\_\_, 20\_\_\_\_\_.

\_\_\_\_\_  
Notary Signature

\_\_\_\_\_  
Applicant Signature

ALL SELF CERTIFICATIONS SUBJECT TO FUTURE REINSPECTION

FOR OFFICE USE ONLY

Team #: \_\_\_\_\_ Municipal Code: \_\_\_\_\_ Log Number: \_\_\_\_\_ Check Number: \_\_\_\_\_

**WHERE TO LOCATE SMOKE ALARMS:**

Alarms are to be located on every level of a residence, (basement, first floor, second floor) excluding crawl spaces and unfinished attics, and in every separate sleeping area, between sleeping areas and living areas such as the kitchen, garage, basement or utility room and in each bedroom. In homes with only one sleeping area on one floor, an alarm is to be placed in the hallway outside each sleeping areas. In single floor homes with two separate sleeping areas, two alarms are required, outside each sleeping areas. In multi-level homes, alarms are to be located outside sleeping areas and at every finished level of the home. Basement level alarms are to be located in close proximity to the bottom of basement stairwells.

**WHERE NOT TO LOCATE SMOKE ALARMS:**

To avoid false alarms and/or improper operation, avoid installation of smoke detectors in the following areas:

Kitchens-smoke from cooking may cause nuisance alarm. - Minimum 10 Feet away

Bathrooms -excessive steam from a shower may cause a nuisance alarm - Minimum 36" Away

Near forced air ducts-used for heating or air conditioning-air movement may prevent smoke from reaching detector - Minimum 36" Away.

The peak of an "A" frame type of ceiling-No more than 36" Down from the peak.

Wall Mounted no more than 12" down from the ceiling

**FURTHER INFORMATION ON ALARM PLACEMENT:**

For further information about alarm placement consult manufacturers installation instructions.

**CARBON MONOXIDE ALARMS** are to be located in every separate sleeping area that contains a fuel fired appliance and immediately outside, within 10 feet of bedrooms that do not contain a fuel fired appliance. Also consult with the manufacturer's instructions.

**WHERE TO LOCATE FIRE EXTINGUISHER:**

Within 10 feet of the kitchen and located in the exit or travel path; and is visible and in a readily accessible location. The top of the fire extinguisher is not more than 5 feet above the floor and is mounted using manufactures hanger or brackets. Minimum size of 2A:10B:C and weigh no more than 10 pounds, is accompanied with the owners manual or with the proper written instructions. The extinguisher is listed, labeled, charged and operable. The extinguisher must have been serviced and tagged by a contractor certified by the New Jersey Division of Fire Safety within the past 12 months or seller must provide a recent proof of purchasing receipt.